

Part Number

WAVE CABLE 

WC-LOCK-L4-2C18N-2C22S-XX-B2CA

18 AWG 2 CORE + 22 AWG 2 CORE SCREENED LOW SMOKE ZERO HALOGEN CABLE

Internal Ripcord • Flexible copper conductor cores •
B2ca fire rating (CPR)

Version Number
V1.0

Date
03/07/26

CABLE USE CASE

Lock Power & Signal/Lock Status
Monitoring

CABLE CONSTRUCTION

2x 18 AWG, 2x 22 AWG Shielded

INSULATION

Extruded LSZH (Low Smoke Zero
Halogen)

OVERALL SHIELD


Aluminium/polyester foil shield

RIPCORD

Easy-strip ripcord for quick sheath
removal.

SHEATH

Extruded LSZH (Low Smoke Zero
Halogen)



● Conductor • ■ Collective Screen • ▨ Outer Sheath
■ Core (22AWG) • ■ Core (18AWG) • ● Ripcord

ELECTRICAL CHARACTERISTICS @20°C

Voltage	300 V
Maximum DC Resistance (22AWG)	59 Ω/km
Maximum DC Resistance (18AWG)	26 Ω/km
Min Insulation Resistance (@20°C)	10 MΩ/km

TEMPERATURE

Operating Temperature Range	-25 to 75 °C
-----------------------------	--------------

PHYSICAL

Minimum Bend Radius	10 x Ø
---------------------	--------

FIRE PERFORMANCE

CPR Classification	B2ca
--------------------	------

5.20mm
(To Scale)



WC-LOCK-L4-2C18N-2C22S-BK-B2CA

INSULATION DIAMETER

22 AWG	1.35 mm
18 AWG	1.72 mm

OUTER SHEATH DIAMETER

5.20 mm

OUTER SHEATH COLOUR

■ Black

Also available in other colours:

								
WH	YL	VT	OR	GR	BL	BK	RD	GY

Scan To Enquire

Or contact us on:
sales@wavecables.com
www.wavecable.com/contact

