

Part Number

WAVE CABLE 

WC-WIEG-W6-3P22S-XX-CCA

22 AWG 3 PAIR SCREENED LOW SMOKE ZERO HALOGEN CABLE

Internal Ripcord • Flexible copper conductor cores •
Cca fire rating (CPR)

Version Number
V1.0

Date
03/07/26



● Conductor •  Collective Screen •  Outer Sheath

■ Pair •  Pair •  Pair •  Pair •  Ripcord

ELECTRICAL CHARACTERISTICS @20°C

Voltage	300 V
Max Conductor Resistance (@20°C)	59 Ω/km
Min Insulation Resistance (@20°C)	M10 Ω/km
Maximum Mutual Capacitance	250 pF/m
Maximum L/R Ratio	25 μH/Ω

TEMPERATURE

Operating Temperature Range	-25 to 75 °C
-----------------------------	--------------


PHYSICAL

Minimum Bend Radius	10 x Ø
---------------------	--------

FIRE PERFORMANCE

CPR Classification	Cca
--------------------	-----

6.33mm
(To Scale)



WC-WIEG-W6-3P22S-BK-CCA

CABLE USE CASE

Card Readers, Biometric Readers
-Wiegand Protocol

CABLE CONSTRUCTION

6x 22 AWG, 3xTwisted pair, overall foil shielded

INSULATION

Extruded LSZH (Low Smoke Zero Halogen) to EN 50363 T16/T17

OVERALL SHIELD

Aluminium/polyester foil shield

RIPCORD

Easy-strip ripcord for quick sheath removal.

TWISTING

2 Cores Twisted Together to Form a Pair

SHEATH

Extruded LSZH (Low Smoke Zero Halogen).

NOMINAL DIMENSIONS

Conductor Gauge	22 AWG
Insulation Diameter	1.35mm
Outer Sheath Diameter	6.33mm

OUTER SHEATH COLOUR

■ Black

Also available in other colours:

								
WH	YL	VT	OR	GR	BL	BK	RD	GY

Scan To Enquire

Or contact us on:

sales@wavecables.com
www.wavecable.com/contact

